

Exit Boxes



Maintained/Non-Maintained LED emergency Exit boxes for use in general retail and commercial applications for emergency lighting requirements.

- 12 month warranty as standard
- Constructed using metal powdercoated base and polycarbonate covers with in-built UV filter to protect against discolouration over time
- Supplied with LED light source
- Supplied with a down arrow legend as standard
- Dual Exit box, can be operated as maintained and non-maintained
- EN60598-2-2 Compliant

Voltage	220-240V 50Hz
Battery	2.4V 4.5AH
Lamp	LED Strip
Power	6W
Operating Temperature	-10°C to +40°C
Emergency Duration	>3 Hours
Recharging time	24 hours

Product Code	Description	Wattage	Lumen Output	Dimensions (mm)
MGEXITML	Maintained LED Exit Box	6W	550lm	390x187x60
MGDEXITML	Decorative White Maintained LED Exit Box	6W	550lm	420x220x65
MGDSCEXITML	Decorative Chrome Maintained LED Exit Box	6W	550lm	420x220x65
MGEXITMLLED/65	IP65 Maintained LED Exit Box	6W	550lm	390x187x60

Additional Item	Application
LGDL	Left Legend for Exit Boxes
LGDR	Right Legend for Exit Boxes
LGDL/65	Left Legend for IP65 Boxes
LGDR/65	Right Legend for IP65 Boxes