

## Coolfin LED Flood Light



Our Coolfin high powered flood light is specifically designed to stay cool, therefore ensuring a long and productive life. This is down to it's unique heat dissipation fins situated on the back of the fitting

The Coolfin uses 2<sup>nd</sup> generation SMD technology. This enables wider beam angles to be achieved making them less directional than other types of diodes which require an epoxy coating to focus the light.

SMD configuration is simpler making them more reliable giving up to 50,000 hours lamp life.

Product Code	Wattage	Lumens	Dimensions (mm) L x W x H
MG-CLF-10	10W	1000	158 X 132 X 53
MG-CLF-20	20W	2000	203 X 176 X 64
MG-CLF-30	30W	3000	219 X 191 X 64
MG-CLF-50	50W	5000	281 X 220 X 117
MG-CLF-70	70W	7000	281 X 220 X 117
MG-CLF-80	80W	8000	281 X 220 X 117
MG-CLF-100	100W	10,000	309 X 267 X 182
MG-CLF-120	120W	12,000	309 X 267 X 182
MG-CLF-150	150W	15,000	364 X 298 X 186
MG-CLF-200	200W	20,000	464 X 344 X 196

Colour Temperature	6000K (3000K and 4000K available to order)
CRI	Ra>80
Beam Angle	110°
Working Temperature	-20°C to +40°C
Power Factor	0.9
Warranty	3 Years
IP Rating	IP65